

## Strapping machine

### *Description*

This machine is the most general purpose type, featuring a high strapping speed and a low failure rate. The amount of strap storage can be freely adjusted based on the dimensions of the bow frame and the dimensions can also be selected freely according to the customer's needs.

### Applications

Oiling is completely unnecessary, which simplifies maintenance Style of bundling: Single and multiple-band parallel binding, both manual and automatic continuous bundling, special switch, foot switch.

### *Technical specifications*

|                |                                  |
|----------------|----------------------------------|
| Strap          | PP strap                         |
| Strap width    | 9,10,12,16,19 mm to be specified |
| Machine weight | 220kgs                           |
| Machine size   | 1410x600x1540(LxDxH) mm          |
| Arch width(mm) | 850x600(WxH) mm                  |
| Strap speed    | 2.3 cycles / min.                |
| Tension        | 5-80 kgs                         |
| Table Height   | 820 mm                           |
| Power supply   | 110v/220v,50/60hz,850 W          |



August 2015

**M.A.I. SAS**

15, rue de la justice  
75020 Paris  
France

**[www.maiparis.com](http://www.maiparis.com)**

Tél. (33) 01 43 43 24 74  
Fax (33) 01 43 43 25 70  
[contact@maiparis.com](mailto:contact@maiparis.com)

Note that product specifications are subject to change without notice and versions of products shown on this site may not yet be available in your local market. While we try to provide the most accurate information available, we cannot be responsible for typographical errors on the site